

AD-A188 415

USER'S MANUAL FOR GENERATING SUPERSONIC DATA BASES FOR
MILITARY OPERATION (U) SPECTRUM SCIENCES AND SOFTWARE
INC FORT WALTON BEACH FL R E LEBLANC 15 OCT 86


1/1


UNCLASSIFIED

SSS-ER-86-06 AMRL-TR-87-031

F/G 12/5

NL





MICROCOPY RESOLUTION TEST CHART

DTIC FILE COPY



**USER'S MANUAL FOR GENERATING SUPERSONIC DATA BASES
FOR MILITARY OPERATIONS AREAS**

ROBERT E. LeBLANC

SPECTRUM SCIENCES & SOFTWARE, INC.
2004-B LEWIS TURNER BLVD.
FORT WALTON BEACH, FL 32548

DTIC
ELECTE
DEC 15 1987
S D

OCTOBER 1986

Approved for public release; distribution is unlimited.


NOISE AND SONIC BOOM IMPACT TECHNOLOGY (NSBIT) ADPO
HUMAN SYSTEMS DIVISION
AIR FORCE SYSTEMS COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433-6573

87 12 9 136


NOTICE

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawing, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This technical report has been reviewed and is approved for publication.


GERAL L. LONG, Lt Col, USAF
NSBIT Program Manager

FOR THE COMMANDER


MICHAEL G. MACNAUGHTON, Col, USAF, BSC
Director of Systems Acquisition
Research, Development & Acquisition
Aerospace Medical Division

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) SSS-ER-86-06			5. MONITORING ORGANIZATION REPORT NUMBER(S) AAMRL-TR-87-031		
6a. NAME OF PERFORMING ORGANIZATION Spectrum Sciences and Software Inc.		6b. OFFICE SYMBOL (If applicable)		7a. NAME OF MONITORING ORGANIZATION Noise & Sonic Boom Impact Technology (NSBIT) Program, Human Systemes Division	
6c. ADDRESS (City, State and ZIP Code) 2004 - B Lewis Blvd Fort Walton Beach, Florida 32548			7b. ADDRESS (City, State and ZIP Code) Brooks AFB TX 78235		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION Directorate of Environmental Planning		8b. OFFICE SYMBOL (If applicable) DEV		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER Control No. F08637-84-D0002 5010	
6c. ADDRESS (City, State and ZIP Code) Air Force Engineering and Services Center Tyndall Air Force Base, Florida 32403			10. SOURCE OF FUNDING NOS.		
			PROGRAM ELEMENT NO. 63723F		PROJECT NO. 3037
			TASK NO.		WORK UNIT NO.
11. TITLE (Include Security Classification) User Manual for Generating Supersonic Data Bases for Military Operations Areas					
12. PERSONAL AUTHOR(S) Robert E Leblanc					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM 1/15/86 TO 10/15/86		14. DATE OF REPORT (Yr., Mo., Day) 86 Oct 15	
				15. PAGE COUNT 88	
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB. GR.	Supersonic ACMI Data Bases		
20	01		Military Operating Areas		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>This report documents the development of supersonic data bases for five military operations areas (MOAs) and presents a user's guide to the two programs that were used to develop the data bases. Data bases were developed for Holloman, Luke, Oceana, Tyndall and Nellis MOAs. These data bases were generated on the Tyndall AFB Cyber Computer using two computer programs (MOAOPS and BOOM-MAP) developed by BBN Laboratories that extract and analyze data from the Tactical Air Crew Training Systems/Air Combat Maneuvering Instrumentation (TACTS/ACMI) manufactured by Cubic Corporation. The TACTS/ACMI system digitizes various positional and performance parameters of the aircraft on the range at frequent intervals for later replay in graphic or tabular form during aircrew debriefings.</p> <p>The MOAOPS program extracts information from TACTS/ACMI mission standard data tapes and compiles a library of engineering data concerning the supersonic operations. The</p>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS <input type="checkbox"/>			21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED		
22a. NAME OF RESPONSIBLE INDIVIDUAL Lt Col GERAL LONG			22b. TELEPHONE NUMBER (Include Area Code) (513) 255-8416		22c. OFFICE SYMBOL AAMRL/CC(NSBIT)

DD FORM 1473, 83 APR

EDITION OF 1 JAN 73 IS OBSOLETE.

UNCLASSIFIED


SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

BOOM-MAP program calculates various statistics on the supersonic operations. It also calculates expected sonic boom levels on the ground based on the extracted information.

The results of the work performed on this contract verify the production capability of the MOAOPS and BOOM-MAP programs for extracting and analyzing data from TACTS/ACMI data tapes. Output from the BOOM-MAP program in terms of supersonic and boom producing flight track maps and noise contour maps, provide the environmental and range planner with important and useful tools to analyze MOA operations.



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

ABSTRACT

This report documents the development of supersonic data bases for five military operations areas (MOAs) and presents a user's guide to the two programs that were used to develop the data bases. Data bases were developed for Holloman, Luke, Oceana, Tyndall and Nellis MOAs. These data bases were generated on the Tyndall AFB Cyber Computer using two computer programs (MOAOPS and BOOM-MAP) developed by BBN Laboratories that extract and analyze data from the Tactical Air Crew Training Systems/Air Combat Maneuvering Instrumentation (TACTS/ACMI) manufactured by Cubic Corporation. The TACTS/ACMI system digitizes various positional and performance parameters of the aircraft on the range at frequent intervals for later replay in graphic or tabular form during aircrew debriefings.

The MOAOPS program extracts information from TACTS/ACMI mission standard data tapes and compiles a library of engineering data concerning the supersonic operations. The BOOM-MAP program calculates various statistics on the supersonic operations. It also calculates expected sonic boom levels on the ground based on the extracted information.

The results of the work performed on this contract verify the production capability of the MOAOPS and BOOM-MAP programs for extracting and analyzing data from TACTS/ACMI data tapes. Output from the BOOM-MAP program in terms of supersonic and boom producing flight track maps and noise contour maps, provide the environmental and range planner with important and useful tools to analyze MOA operations.

Accession For	
NTIS CRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



SUMMARY

This report documents the development of supersonic data bases for five military operations areas (MOAs) and presents a user's guide to the two programs that were used to develop the data bases. Data bases were developed for Holloman, Luke, Oceana, Tyndall and Nellis MOAs. These data bases were generated on the Tyndall AFB Cyber Computer using two computer programs (MOAOPS and BOOM-MAP) developed by BBN Laboratories that extract and analyze data from the Tactical Air Crew Training Systems/Air Combat Maneuvering Instrumentation (TACTS/ACMI) manufactured by Cubic Corporation. The TACTS/ACMI system digitizes various positional and performance parameters of the aircraft on the range at frequent intervals for later replay in graphic or tabular form during aircrew debriefings.

The MOAOPS program extracts information from TACTS/ACMI mission standard data tapes and compiles a library of engineering data concerning the supersonic operations. The BOOM-MAP program calculates various statistics on the supersonic operations. It also calculates expected sonic boom levels on the ground based on the extracted information.

The MOAOPS program was originally written to read data directly from TACTS/ACMI mission tapes; however, this was not possible on the Tyndall computer. Data on the mission tape was first copied to a disk file before executing the MOAOPS program. This restriction only impacts data extraction when a single mission is contained on two tapes because of limited storage capacity on the Tyndall computer. The user must obtain a dedicated disk pack for two mission tapes.

The results of the work performed on this contract verify the production capability of the MOAOPS and BOOM-MAP programs for extracting and analyzing data from TACTS/ACMI data tapes. Output from the BOOM-MAP program in terms of supersonic and boom producing flight track maps and noise contour maps, provide the environmental and range planner with important and useful tools to analyze MOA operations.

TABLE OF CONTENTS

Abstract	i
Summary	ii
Table of Contents	iii
List of Figures	iv
List of Tables	v
 I. OVERVIEW	 1
 II. SUPERSONIC DATA BASE GENERATION AND MAINTENANCE	 4
2.1 Introduction	4
2.2 File Management on the Tyndall Cyber	5
2.3 Program EXTRACT	5
2.3.1 General Description	5
2.3.2 Program EXTRACT Input Data	8
2.3.3 Program EXTRACT Batch File Examples	9
2.3.4 Program EXTRACT Output Data	11
2.4 Program DELETE	13
2.4.1 General Description	13
2.4.2 Program DELETE Input Data	14
2.4.3 Program DELETE Batch File Examples	15
 III. BOOM-MAP, SUPERSONIC AIRCRAFT ACTIVITY SUMMARY AND BOOM STRENGTH PREDICTION PROGRAM	 24
3.1 General Description	24
3.2 BOOM-MAP Input Data	28
3.2.1 TITLE Card	28
3.2.2 Library Data Qualifier Cards	28
3.2.3 Output Product Specification Cards	32
3.2.4 Input Example	35
3.3 BOOM-MAP Batch File Examples	37
3.4 BOOM-MAP Output	39
 IV. REFERENCES	 42
 V. APPENDICES	

LIST OF FIGURES

	<u>Page</u>
Figure 3.1 - Functional Relationships Between Elements of BOOM-MAP Compute Program	26

LIST OF TABLES

	<u>Page</u>
Table 2.1 - Batch File for a Creation Run	10
Table 2.2 - Batch File for an Update Run.	12
Table 2.3 - Batch File for Running the DELETE Program Using the DELETE Mode.	16
Table 2.4 - List of Batch Commands Required to Run DELETE in the "CHANGE" Mode.	18
Table 2.5 - Sample Interactive Session Using the CHANGE Mode of the DELETE Program	19
Table 2.6 - Example of TAPE 1 Produced by the "CHANGE" Mode of the DELETE Program	21
Table 3.1 - Batch File Example to Run BOOM-MAP	38

SECTION 1. OVERVIEW

This report documents the development of supersonic data bases for five military operations areas (MOAs) and presents a user's guide to the two programs that were used to develop the data bases. Data bases were developed for Holloman, Luke, Oceana, Tyndall and Nellis MOAs. These data bases were generated using two computer programs (MOAOPS and BOOM-MAP) developed by BBN Laboratories that extract and analyze data from the Tactical Air Crew Training Systems/Air Combat Maneuvering Instrumentation (TACTS/ACMI) manufactured by Cubic Corporation. The TACTS/ACMI system digitizes various positional and performance parameters of the aircraft on the range at frequent intervals for later replay in graphic or tabular form during aircrew debriefings.

The MOAOPS program extracts information from TACTS/ACMI mission standard data tapes and compiles a library of information concerning the supersonic operations. The BOOM-MAP program calculates various statistics on the supersonic operations. It also calculates expected sonic boom levels on the ground based on the extracted information.

This work was accomplished using the Tyndall AFB Cyber 170 computer and Calcomp plotter. The two BBN programs, MOAOPS and BOOM-MAP, required modification before they could be used. Section 2 discusses the generation and modification of the supersonic data bases using the MOAOPS program to extract and modify aircraft mission data from TACTS/ACMI mission tapes. Section 3 discusses the generation of output plots using the BOOM-MAP program to analyze the supersonic data bases and to generate the necessary input files for the General Purpose Contouring Program (GPCP II). Appendix A contains examples of

output from the MOAOPS program and includes mission and aircraft indexes for each MOA. Appendix B contains examples of output from the BOOM-MAP program and plots, depicting supersonic flight tracks, sonic boom producing flight tracks, overpressure contours, CSEL contours and CLDN contours obtained from the data bases. Plots are included for each MOA except Oceana. The BOOM-MAP program would not accept data from the Oceana LIBRY file. In addition, BOOM-MAP would not accept some of the data in the Tyndall LIBRY file. These two problems are being investigated by BBN Laboratories. The user is cautioned that all plots have been reduced for this report; therefore, the scale is not accurate. Additional information concerning MOAOP and BOOM-MAP can be found in the BBN User's Guide written by Wilby [1].

SECTION 2 SUPERSONIC DATA BASE GENERATION AND MAINTENANCE

2.1 INTRODUCTION

This section will outline the procedures used to generate the supersonic data bases for Holloman, Luke, Oceana, Nellis and Tyndall MOAs. The MOAOP program actually consists of two separate programs: EXTRACT and DELETE. EXTRACT contains the code to extract data from the TACTS/ACMI mission tapes and DELETE is used to delete references from the INDEX file and to change mission names on existing index and library files. The EXTRACT program generates three files : two index files ("INDEX" and "MINDEX") and one library file ("LIBRY").

The MINDEX file contains a list of all mission numbers analyzed from TACTS/ACMI tapes. The MINDEX file serves as a record of missions analyzed and is updated when additional TACTS/ACMI tapes are read and when the DELETE program is run in the "CHANGE" mode. MINDEX is not used by the BOOM-MAP program. The INDEX file contains mission number, date, mission start and end time, TACTS/ACMI site name and number, aircraft type and tail number, the total number of records written to the LIBRY file, and the number of supersonic records written to the LIBRY file. The LIBRY file contains specific time, position, G load and velocity for each aircraft. Although aircraft information is recorded for each aircraft at 100 to 200 millisecond intervals, data was extracted from the TACTS/ACMI mission tapes at 1.5 second intervals. Only supersonic data was extracted from the TACTS/ACMI tapes. However, the EXTRACT program will still create a three record entry in the LIBRY file for non-supersonic data. These records can be deleted using the DELETE program but they will not cause any problems if they are left in the INDEX and LIBRY files.

2.2 File Management on the Tyndall Cyber

The Tyndall Cyber 170/730 computer, hereafter referred to as Cyber, current operating system is Nos 2.4.3 level 647. All permanent files on the Cyber are classified according to the manner in which they are accessed: indirect or direct access. These two access methods should not be confused with file types. The EXTRACT program generates two different file types: sequential and direct access. The INDEX and LIBRY files are direct access and the MINDEX file is sequential. The user is cautioned that a direct access type file e.g., an INDEX or LIBRY file cannot be altered with a text editor. You can examine a direct access file with the XEDIT editor but you must exit XEDIT with the "STOP" command. If you exit XEDIT with the "QUIT" command you may destroy the file key and render the file useless.

The access mode is determined by the command used to make the file permanent. How the file is made permanent also determines the command you must enter to access the file. If the user is not familiar with the permanent file storage and access commands they can be found in NOS Version 2 Reference Set, Volume 2. The INDEX and LIBRY files are usually stored as direct access permanent files while the MINDEX file is stored as an indirect access file. The Cyber has the NOS/BE "STORE" command installed which will automatically determine the storage method depending on file size. The user can store the MINDEX file as a direct access file.

2.3 Program EXTRACT

2.3.1 General Description

The EXTRACT program reads a TACTS/ACMI Mission Standard Data tape, extracts relevant information and appends this information to either a

new or existing data base. The TACTS/ACMI mission tapes contain data on up to 8 instrumented aircraft flying a mission on the MOA. Among the data collected is real time information on aircraft position, velocity and acceleration, updated at intervals of 100 to 200 milliseconds. The program extracts this data at approximately 1.5 second intervals in order to minimize both the time taken to read the tapes and the quantity of information to be stored. Storage capacity is extremely limited on the Cyber.

The number of tapes required to record an entire mission depends on the length of the mission and the number of aircraft involved. The EXTRACT program is designed to read data directly from TACTS/ACMI tapes; however, this is not possible on the Cyber. The TACTS/ACMI tape must be copied to a disk file before the data can be extracted. This does not cause any difficulty unless a single mission is on two tapes. Because of the size of the disk file generated by two TACTS/ACMI tapes, the user must obtain a dedicated disk pack and increased storage allocation from AFESC/SI. This assumes the user is using the Tyndall Cyber.

The information is then appended to either a new or an existing library file, which accumulates the information from all the mission tapes analyzed. The library file is indexed, so that a particular mission, aircraft type, etc., can be accessed by the sonic boom analysis program.

Two index files are formed. The mission index file (MINDEX) contains only the mission names, dates and site location for all the tapes analyzed. The second index (INDEX) contains information on every aircraft flying for every mission analyzed, such as aircraft type, aircraft tail number, starting and ending time of the mission.

Each entry in this index file is associated with a time series of data stored in the library file, and the appropriate record numbers for the library file access are stored in the index file. This index file is then used by the sonic boom analysis program to retrieve the appropriate flights to be analyzed.

During a mission, it is possible that changes may occur in the aircraft flying, or that erroneous data has been included in the mission tape and later corrected. The program detects any change in the number of aircraft flying, aircraft type or aircraft tail numbers and signifies the start of a new mission segment when this occurs. The index file contains one entry for each aircraft flying in each mission segment. The library file has an associated time series of data for each aircraft flying each mission segment.

Two choices are available for the data extraction program.

1. Only supersonic data ($M > 0.99$) may be stored in the library file or all data (subsonic and supersonic) may be stored. It is important to keep the index and library files for these two cases distinctly separate, as the sonic boom analysis program uses only the supersonic data.
2. The sonic boom analysis program only requires data at time intervals of approximately 1.5 seconds for reasonable accuracy. However, an option in the data extraction program is available to read and store data in the library file at 100 or 200 millisecond intervals. The intention is to make it possible to analyze a few flight tracks in great detail if necessary. This option is not recommended for building a data base of many missions as the quantity of data could

become prohibitively large and should not be used for the BOOM-MAP data base.

In addition to the data extraction program, a program to delete entries from the index files has been written. The program does not delete any information from the library file, but deletes the index entry and all references giving access to the library information associated with the index entry. The index deletion feature is necessary in case mission tapes have been analyzed that should not form part of the permanent data base, or some index entries show errors that occurred on the TACTS/ACMI tapes.

2.3.2 Program EXTRACT Input Data

Only 5 lines are required for input, each in character form, contained in apostrophes.

1. 'SUPERSONIC DATA ONLY' or 'ALL DATA SELECTED'. The first option selects dynamic records for Mach number $M > 0.99$. The second option selects subsonic and supersonic data, with no restriction on Mach number.
2. 'DATA AT =1 SECOND INTERVALS' or 'ALL DYNAMIC DATA'. The first option reads dynamic data records at approximately 1.5 second intervals. The second option reads all the dynamic data output at 100 or 100 millisecond intervals, but should not be used in forming the supersonic database for BOOM-MAP.
3. 'NEW INDEX AND LIBRARY FILES TO BE CREATED' or 'OLD INDEX AND LIBRARY FILES TO BE USED'. The first option is used only for the first mission tape analyzed in

starting the library and index files. The second option is used for the second mission tape analyzed and thereafter.

4. 'FULL INDEX PRINTED' or 'UPDATED INDEX ONLY'. As many tapes are analyzed, the index file may get quite large. The 'FULL' index prints the whole file, while 'UPDATED' prints only the mission currently being analyzed.
5. 'ONE = NUMBER OF FIRST TAPE REEL READ' or 'ANY = NUMBER OF FIRST TAPE REEL READ'. If the option 'ONE' is used, the program will stop unless tape reel number 1 is mounted. The option 'ANY', permits any reel number to be the first tape reel, but multiple tape reels must still follow in sequence.

2.3.3 Program EXTRACT Batch File Examples

The job control language (JCL) and the input data required to extract information from a TACTS/ACMI mission tape using the EXTRACT program is shown in Table 2.1. The batch file in Table 2.1 was used to analyze the first mission tape for the Tyndall MOA. The index and library files are all direct access permanent files because the "DEFINE" command was used to create them. Since the MINDEX is a small file it could have been declared an indirect access permanent file by using the "SAVE" command. It is up to the user to determine the permanent file storage type for the MINDEX file. As mentioned earlier the size of the INDEX and LIBRY file dictate that these files will be direct access permanent files. In this example, the file "EXTRACT" in the statement "GET, LGO = EXTRACT", is the executable code for the program EXTRACT. The user can compile the DELETE PROGRAM for each run

```

/JOB
SPECTUM, T400.
/USER
CHARGE(*)
SETTL, 5000.
*
*   CREATION BATCH FILE FOR TYNDALL
*
DEFINE, INDEX=TYNINDEX.
DEFINE, LIBRY=TYNLIB.
DEFINE, MINDEX=TYNMDEX.
LABEL, TAPE, VSN=000004, NT, D=PE, LB=KU, F=L, PO=R.
COPY, I=TAPE, O=TAPE1, BS=2000.
UNLOAD, TAPE.
REWIND, TAPE1.
GET, LGO=EXTRACT.
LDSET, PRESET=ZERO.
LGO(*PL=30000)
RETURN, TAPE1, MINDEX, INDEX, LIBRY.
DAYFILE.
REWIND, OUTPUT.
ROUTE, OUTPUT, DC=PR.
/EOR
'SUPERSONIC DATA ONLY'
'DATA AT>1 SECOND INTERVALS'
'NEW INDEX AND LIBRARY FILES TO BE USED'
'FULL INDEX PRINTED'
'ANY = NUMBER OF FIRST TAPE REEL READ'
/EOF

```

Table 2.1 Batch file for a creation run.

but is not as efficient as using the LGO FILE. An example of a batch file to update the Tyndall MOA file is depicted in Table 2.2. The only change required in the input data is to change "new" to "old" in the third line. In the JCL, the "DEFINE" commands have been replaced by "ATTACH" commands because the files were created on the initial run.

2.3.4 Program EXTRACT Output Data

Examples of the output from program EXTRACT are given in Appendix A. Table A-1 contains information on the mission tape being analyzed and includes any warning messages that may occur during the analysis. These include parity errors, unidentified block types, etc., which may be useful to determine if the data in a mission segment is suspect. This table should be scrutinized to determine whether any mission segments should be deleted from the index at a later date. The possible reasons for deletions are:

1. Obvious errors in aircraft data, such as omission of A/C type.
2. Many parity errors, indicating a poor quality tape and insufficient data.
3. False start of a mission (due to data omission or poor tape) giving a very short initial mission segment, which could be ignored.
4. No supersonic activity.

Table A-2 is a direct echo of the information stored on the library file and has been deliberately left in the same format.

Table A-3 is a listing of the index file, either the FULL index or the UPDATED index only (the mission currently being analyzed), as specified by the input.

```

/JOB
SPECTUM, T400.
/USER
CHARGE(*)
SETTL, 5000.
*
*   UPDATE BATCH FILE FOR TYNDALL
*
ATTACH, INDEX=TYNINDEX/M=W.
ATTACH, LIBRY=TYNLIB/M=W.
ATTACH, MINDEX=TYNMDEX/M=W.
LABEL, TAPE, VSN=000004, NT, D=PE, LB=KU, F=L, PO=R.
COPY, I=TAPE, O=TAPE1, BS=2000.
UNLOAD, TAPE.
REWIND, TAPE1.
GET, LGO=EXTRACT.
LDSET, PRESET=ZERO.
LGO(*PL=30000)
RETURN, TAPE1, MINDEX, INDEX, LIBRY.
DAYFILE.
REWIND, OUTPUT.
ROUTE, OUTPUT, DC=PR.
/EOB
'SUPERSONIC DATA ONLY'
'DATA AT>1 SECOND INTERVALS'
'OLD INDEX AND LIBRARY FILES TO BE USED'
'FULL INDEX PRINTED'
'ANY = NUMBER OF FIRST TAPE REEL READ'
/EOF

```

Table 2.2 Batch file for an update run.

Table A-4 is a listing of the mission tapes analyzed for the database.

The remainder of Appendix A contains current index and mission index files for all five MOAs that were created under this contract.

2.4 Program DELETE

2.4.1 General Description

The DELETE program operates in one of two modes: the "delete" mode and the "change" mode. When using the DELETE program to delete data from the index file, the job should be run in the batch mode. The "change" option should be run interactively. In order to delete data on a specific mission or aircraft from the database 'LIBRY', created using program EXTRACT, it is only necessary to delete all references to that specific data from the index files 'INDEX' and 'MINDEX'. The program DELETE reads the existing files 'INDEX' and 'MINDEX', modifies them as selected by the input and outputs new files 'INDEXN' and 'MINDEXN' in the same format with the appropriate index entries deleted.

The file 'INDEXN' should again be defined as a direct access file for permanent storage if the file 'INDEX' was previously so defined. The users' permanent file names used for storing the existing files 'INDEX' and 'MINDEX' and the new modified 'INDEXN' and 'MINDEXN' files should differ. On completion of the program, the output will list the index entries deleted and this output should be checked before purging the old 'INDEX' file and thus permanently preventing access to the deleted entries. Typically the deletions will not be necessary until the database is to be accessed by the BOOM-MAP program. A copy of the full, unmodified index should be kept on the back-up magnetic tape.

The DELETE program can also be used to change mission names in the "LIBRY" and "INDEX" files. This feature is extremely useful if you want to analyze data for a particular type of mission. The change mode will allow you to change selected mission names. The requested mission names are changed in the "INDEX" and "LIBRY" files as well as the date and time in the first record of these two files. Only the date and time in the first record is changed in the new "MINDEX" file. The change mode is designed to be operated interactively. A record of all changes made during the session are written to a local file named "TAPE1". An example of file TAPE1 will be shown later in Section 2.4.3. This file should be reviewed before the old "LIBRY" and "INDEX" files are purged and the new files catalogued.

2.4.2 Program DELETE Input Data for the "delete" Mode

The data for the "delete" mode is input in character strings or integers, one entry per line. All character strings must be enclosed within single quotation marks.

'MISSION NAMES TO BE DELETED'

(Max No. 25)

'5203-15'

An example of a mission name.

.

This must match exactly the entries in

.

the mission index and library index

.

files.

.

'ENTRY NUMBERS TO BE DELETED'

(Max No. 50)

1 Examples of entries to be deleted, one
.
.
.
.
45 These refer to the INDEX file line

. numbers.
.
.
.
39

/EOF End of file mark, signified end of entries.

When running the DELETE program in the "change" mode the user will be prompted for the input. The program asks you to verify that the correct files were attached. The program then asks for the "INDEX" file entry number of the mission name you want to change. After confirming the correct mission name, you are asked to enter the new mission name. The new mission name is written in the new "LIBRY" and "INDEX" files.

2.4.3 Program DELETE Batch File Example for "delete" Mode

Table 2.3 shows a sample batch file that can be used by the DELETE program in the "delete" mode. This example deletes mission numbers and particular entry numbers in the reference index file. In fact, this particular example deletes all non-supersonic data from the Tyndall INDEX file, TYNINDEX, listed in Table A-13. Notice that all character input data is enclosed in single quotation marks. The entry numbers should be left justified. There is no need to attach the

```

/JOB
SPECTUM,T400.
/USER
CHARGE(*)
SETTL,5000.
*
*   BATCH FILE FOR DELETE PROGRAM
*
ATTACH,INDEX=TYNIDEX.
ATTACH,LIBRY=TYNLIB.
GET,LGO=DELETER.
LDSET,PRESET=ZERO.
LGO(*PL=30000)
DAYFILE.
REWIND,OUTPUT.
ROUTE,OUTPUT,DC=PR.
/EOR
'MISSION NAMES TO BE DELETED'
'6074-1'
'6169-7'
'6170-7'
'6220-1'
'ENTRY NUMBERS TO BE DELETED'
9
13
14
19
34
35
37
39
40
41
42
44
46
47
52
54
/EOF

```

Table 2.3 Batch file for running the DELETE program using the delete mode.

library file because only the index file is modified; the actual data remains in the library file. Table 2.4 depicts the commands required to run the DELETE program in the "change" mode. The files "INDEXN" and "LIBRYN" are the new index and library files respectively, that are created. File "DELETER" is the binary executable file for the DELETE program. All files must be attached before the program is executed. The last batch command in Table 2.4, "DELETER" executes the program. Table 2.5 illustrates program prompts from a sample session. Although the "delete" mode can be run interactively, this part of the program is not menu driven. It is recommended that the "delete" mode be run only in the batch mode. When using the "change" mode the system prompt is a question mark (?). When answering the first prompt be sure to include your response in single quotation marks ('CHA'). The program uses the date and time of the INDEX and LIBRY files to verify that the correct files have been attached. To change a mission name you must enter the index file entry number for that particular mission. If there is more than one line number for that mission, each line must be entered separately. One line number entry will not change all entries with the same mission number.

If you enter the wrong line number you can enter "N" when the user is asked to verify if the correct mission name has been selected. If a mission number is out of range the program will not accept the number and will request another value. The program is terminated by entering a zero (0) for the line number. During the execution of the program all transactions have been recorded on a local file called TAPE1. This file should be reviewed before discarding the old INDEX and LIBRY files. Of course, the old files can also be retained if the user wants to keep them. Table 2.6 is an example of file TAPE1.

/ATTACH, INDEX=CEAIDEX/M=R
/DEFINE, INDEXN=NEWIDEX
/ATTACH, LIBRY=CEALIB/M=R
/DEFINE, LIBRYN=NEWLIB
/ATTACH, MINDEX=CEAMDEX/M=R
/GET, DELETER
/DELETER

Table 2.4 List of batch commands required to run DELETE
in the 'change' mode.

```

*****
*****
RUN PROGRAM DELETE TO DELETE INDEX ENTRIES AND/OR MISSION NAMES OR TO
CHANGE THE MISSION NAME. THE CHANGE MODE IS RUN INTERACTIVELY
WHILE THE DELETE MODE IS RUN AS A BATCH JOB.

ENTER(INCLUDE QUOTES):
  'CHA' - TO RUN THE CHANGE MODE
  'MIS' - TO RUN THE DELETE MODE (NOT MENU DRIVEN)
? 'CHA'

ORIGINAL INDEX BEFORE CHANGES. DATE 86/06/24. TIME 13.37.36.
ORIGINAL LIBRY FILE BEFORE CHANGES. DATE 86/06/24. TIME 13.37.36.
ARE THE ABOVE FILES THE ONES YOU WANT (Y/N)?
? Y

COPYING THE INDEX FILE FROM INDEX TO INDEXN.
COPYING THE LIBRY FILE FROM LIBRY TO LIBRYN.
ENTER THE INDEX FILE ENTRY NUMBER OF THE MISSION NAME TO BE CHANGED.
ENTER 0 TO EXIT THE CHANGE MODE.
? 1

THE CURRENT MISSION NAME FOR ENTRY 1 IS: LAA603120639
STARTING TIME: 0919 5436 A/C NO. & TYPE: 39 F-4
IS THIS THE CORRECT ENTRY (Y/N)?
? Y

ENTER NEW MISSION NAME -- MAX 16 CHARACTERS LEFT JUSTIFIED:
-----
? DACT

MISSION NAME IS: DACT
IS IT OKAY (Y/N)?
? Y

LIBRY FILE MISSION NAME IN RECORD 2 IS: LAA603120639
IS THIS THE CORRECT RECORD (Y/N)?
? Y

MISSION NAME: LAA603120639 HAS BEEN REPLACED BY
MISSION NAME: DACT IN THE INDEX AND LIBRY FILES.

```

Table 2.5. Sample Interactive Session Using the CHANGE Mode of the DELETE Program.

ENTER THE INDEX FILE ENTRY NUMBER OF THE MISSION NAME TO BE CHANGED.
 ENTER 0 TO EXIT THE CHANGE MODE.
 ? 3

THE CURRENT MISSION NAME FOR ENTRY 3 IS: LAA603120639
 STARTING TIME: 0919 5436 A/C NO. & TYPE: 59
 IS THIS THE CORRECT ENTRY (Y/N)?
 ? Y

ENTER NEW MISSION NAME -- MAX 16 CHARACTERS LEFT JUSTIFIED:

 ? BFM

MISSION NAME IS: BFM
 IS IT OKAY (Y/N)?
 ? Y

LIBRY FILE MISSION NAME IN RECORD 82 IS: LAA603120639
 IS THIS THE CORRECT RECORD (Y/N)?
 ? Y

ENTER THE INDEX FILE ENTRY NUMBER OF THE MISSION NAME TO BE CHANGED.
 ENTER 0 TO EXIT THE CHANGE MODE.
 ? 8

THE CURRENT MISSION NAME FOR ENTRY 8 IS: LAA603110630
 STARTING TIME: 0918 2095 A/C NO. & TYPE: 36 F-14
 IS THIS THE CORRECT ENTRY (Y/N)?
 ? N

ENTER THE INDEX FILE ENTRY NUMBER OF THE MISSION NAME TO BE CHANGED.
 ENTER 0 TO EXIT THE CHANGE MODE.
 ? 15

THE CURRENT MISSION NAME FOR ENTRY 15 IS: LAA603110630
 STARTING TIME: 0914 1392 A/C NO. & TYPE: 59
 IS THIS THE CORRECT ENTRY (Y/N)?
 ? N

ENTER THE INDEX FILE ENTRY NUMBER OF THE MISSION NAME TO BE CHANGED.
 ENTER 0 TO EXIT THE CHANGE MODE.
 ? 55

ENTRY NUMBER 55 IS OUT OF RANGE - TRY AGAIN]

ENTER THE INDEX FILE ENTRY NUMBER OF THE MISSION NAME TO BE CHANGED.
 ENTER 0 TO EXIT THE CHANGE MODE.
 ? 0

CHECK LOG ON FILE TAPE1 BEFORE PURGING THE OLD FILES.

DO NOT FORGET TO REPLACE THE MINDEXN FILE
 AND PURGE THE MINDEX, INDEX AND LIBRY FILES. AS NEEDED.
 STOP 6666

Table 2.5. Continued

ORIGINAL INDEX BEFORE CHANGE. DATE 06/06/74. TIME 13.37.36.
 0 165UP 06/06/74. 13.37.36.

1 LAA603120639	03/12/86	3 OCEANA	091954360947221239F-4	94TH	2	13	10
2 LAA603120639	03/12/86	3 OCEANA	091954360947221236F-14	94TH	15	67	64
3 LAA603120639	03/12/86	3 OCEANA	091954360947221239	VF-4	02	21	18
4 LAA603120639	03/12/86	3 OCEANA	091954360947221230	VF-4	103	46	43
5 LAA603120639	03/12/86	3 OCEANA	091954360947221259	VF-4	149	55	52
6 LAA603100619	03/10/86	3 OCEANA	103959751121351339F-4	71ST	204	257	254
7 LAA603110630	03/11/86	3 OCEANA	091413920918206536F-14	94TH	461	3	0
8 LAA603110630	03/11/86	3 OCEANA	091020950944442936F-14	94TH	464	3	0
9 LAA603110630	03/11/86	3 OCEANA	091413920918206539F-4	94TH	467	3	0
10 LAA603110630	03/11/86	3 OCEANA	091020950944442936F-14	94TH	470	3	0
11 LAA603110630	03/11/86	3 OCEANA	091413920918206539	VF-4	473	3	0
12 LAA603110630	03/11/86	3 OCEANA	091020950944442939	VF-4	476	52	49
13 LAA603110630	03/11/86	3 OCEANA	091413920918206539	VF-4	520	3	0
14 LAA603110630	03/11/86	3 OCEANA	091020950944442939	VF-4	531	7	4
15 LAA603110630	03/11/86	3 OCEANA	091413920918206539	VF-4	530	3	0
16 LAA603110630	03/11/86	3 OCEANA	091020950944442939	VF-4	541	4	1

LOG OF DELETE PROGRAM CHANGE MODE RUN:

MISSION NAME: LAA603120639 HAS BEEN REPLACED BY
 MISSION NAME: DACT IN THE INDEX AND LIBRY FILES.
 MISSION NAME: LAA603120639 HAS BEEN REPLACED BY
 MISSION NAME: BFM IN THE INDEX AND LIBRY FILES.

 * INDEX FILE TO LIBRARY TAPE *
 * FULL INDEX: 06/10/15. *
 * 13.03.00. *
 * SUPERSONIC DATA ONLY *

ENTRY NO	MISSION NAME	MISSION DATE	SITE NO LOCATION	STARTING TIME HR M SEC	FINISHING TIME HR M SEC	A/C TYPE	A/C TAIL NO	STARTING RECORD NO	NO OF RECORDS	NO OF SUPERSONIC RECORDS
1 DACT		03/12/86	3 OCEANA	0919 5436	0947 2212	39 F-4	94TH	2	13	10
2 LAA603120639		03/12/86	3 OCEANA	0919 5436	0947 2212	36 F-14	94TH	15	67	64
3 BFM		03/12/86	3 OCEANA	0919 5436	0947 2212	59	VF-4	02	21	18
4 LAA603120639		03/12/86	3 OCEANA	0919 5436	0947 2212	58	VF-4	103	46	43
5 LAA603120639		03/12/86	3 OCEANA	0919 5436	0947 2212	59	VF-4	149	55	52
6 LAA603100619		03/10/86	3 OCEANA	1039 5975	1121 3313	39 F-4	71ST	204	257	254
7 LAA603110630		03/11/86	3 OCEANA	0914 1392	0918 2065	36 F-14	94TH	461	3	0
8 LAA603110630		03/11/86	3 OCEANA	0910 2095	0944 4429	36 F-14	94TH	464	3	0
9 LAA603110630		03/11/86	3 OCEANA	0914 1392	0918 2065	39 F-4	94TH	467	3	0
10 LAA603110630		03/11/86	3 OCEANA	0910 2095	0944 4429	36 F-14	94TH	470	3	0
11 LAA603110630		03/11/86	3 OCEANA	0914 1392	0918 2065	59	VF-4	473	3	0
12 LAA603110630		03/11/86	3 OCEANA	0910 2095	0944 4429	59	VF-4	476	52	49
13 LAA603110630		03/11/86	3 OCEANA	0914 1392	0918 2065	59	VF-4	520	3	0
14 LAA603110630		03/11/86	3 OCEANA	0910 2095	0944 4429	59	VF-4	531	7	4
15 LAA603110630		03/11/86	3 OCEANA	0914 1392	0918 2065	59	VF-4	530	3	0
16 LAA603110630		03/11/86	3 OCEANA	0910 2095	0944 4429	59	VF-4	541	4	1

Table 2.6. Example of TAPE 1 Produced by the "CHANGE" Mode of the DELETE Program.

PRINT THE FIRST LIBRY RECORD FOR EACH MISSION:

THE FIRST TWO FIELDS ARE THE LIBRY INDEX ENTRY NUMBER AND
THE FIRST LIBRY FILE RECORD NUMBER FOR THAT MISSION SEGMENT.

INDEX ENTRY	LIBRY START	MISSION NAME	MISSION DATE	START TIME	A/C TYPE	A/C TAIL NO
1	2	DACT	03/12/86	0919 5436	F-4	94TH
2	15	LAA603120639	03/12/86	0919 5436	F-14	94TH
3	82	BFH	03/12/86	0919 5436		VF-4
4	103	LAA603120639	03/12/86	0919 5436		VF-4
5	149	LAA603120639	03/12/86	0919 5436		VF-4
6	204	LAA603100619	03/10/86	1039 5975	F-4	71ST
7	461	LAA603110630	03/11/86	0914 1392	F-14	94TH
8	464	LAA603110630	03/11/86	0918 2095	F-14	94TH
9	467	LAA603110630	03/11/86	0914 1392	F-4	94TH
10	470	LAA603110630	03/11/86	0918 2095	F-14	94TH
11	473	LAA603110630	03/11/86	0914 1392		VF-4
12	476	LAA603110630	03/11/86	0918 2095		VF-4
13	528	LAA603110630	03/11/86	0914 1392		VF-4
14	531	LAA603110630	03/11/86	0918 2095		VF-4
15	538	LAA603110630	03/11/86	0914 1392		VF-4
16	541	LAA603110630	03/11/86	0918 2095		VF-4

* MISSION INDEX FILE *
* UPDATED: 86/10/15. *
* 13.03.01. *
* SUPERSONIC DATA ONLY *

MISSION NAME	MISSION DATE	SITE LOCATION
LAA603120639	03/12/86	OCEANA
LAA603100619	03/10/86	OCEANA
LAA603110630	03/11/86	OCEANA

CHECK THE ABOVE MISSION NAME CHANGES BEFORE
PURGING THE OLD MINDEX, INDEX, AND LIBRY FILES.

DON'T FORGET TO REPLACE THE 'MINDEXN' FILE.

EXIT THE CHANGE MODE VERSION OF THE DELETE PROGRAM.

PROGRAM ENDS.

Table 2.6. Continued.

This particular example was generated using the session depicted in Table 2.5.

3.0 BOOM-MAP, SUPERSONIC AIRCRAFT ACTIVITY SUMMARY AND BOOM STRENGTH PREDICTION PROGRAM

3.1 General Description

The BOOM-MAP data analysis computer program accesses the TACTS/ACMI database generated by the MOAOPS computer program discussed in Section 2.0. The data analysis program produces statistical and graphic output describing aircraft position parameters as well as various measures of predicted boom strength. This program utilizes the data available in the TACTS/ACMI flight data library to produce graphic and tabular descriptions of MOA range activity.

Tabular output are produced by the BOOM-MAP program and are output directly to the line printer. To produce graphic output, BOOM-MAP creates a file compatible with California Computer Products' (CALCOMP) General Purpose Contouring Program (GPCP II). GPCP II reads this file and generates the necessary plotter directives on file TAPE II to produce hard copy graphic output.

Users control the database subset to be extracted from the library run through the use of an input data file. Through this file the user specifies:

- 1) the name(s) of the MOA ranges to be considered
- 2) mission names or dates
- 3) bounding times of day
- 4) aircraft types (specific tail numbers optional).

Users also specify desired output products. These include:

- 1) A statistical summary of position, speed, and boom strength variables. This summary includes distribution functions of range x-coordinates and y-coordinates, and the aircraft z-coordinate

(height above the range), all in feet. It also includes a distribution function of effective height (h_e). Distribution functions of Mach number, cutoff Mach number and effective Mach number are also presented. Estimated boom strength distribution functions include peak overpressure (in pounds per square foot), the peak overpressure (in dB, re: 20 microPascals), and the A-weighted sound exposure level (in dB). The estimated boom strength are those calculated directly below the extended aircraft flight trajectory. Also included are root mean square values for effective height, Mach number, effective Mach number, and cutoff Mach number.

- 2) A flight track map depicting ground projections of flight paths during supersonic activity.
- 3) A flight track map depicting ground projections of flight paths during sonic boom producing activity.
- 4) A noise contour map of average C-weighted sound exposure levels (CSEL).
- 5) A noise contour map of C-weighted day/night average levels (CLDN), requiring input of the reference number of daytime operations which will be used to convert CSEL to CLDN.
- 6) A noise contour map of flight averaged peak over-pressures (in pounds per square foot).

Figure 3.1 presents a functional block diagram of the BOOM-MAP software package. The user supplied directives (described in detail in this section) are read first and stored in memory. Information on the library entries are then read one at a time from the library index file and the sortie parameters compared with the qualifiers




Figure 3.1. Functional Relationships Between Elements of BOOM-MAP Compute Program.

provided by the user in the input directives. When a library sortie meets the screening criteria, its time history file is read from the library and the flight is processed by the BOOM-MAP program. A journal is concurrently output to the line printer (one line per sortie) which identifies the mission name, the date, the site location, the sortie starting and ending times, the aircraft type and tail number, the amount of supersonic time and the amount of boom producing time. This journal presents users with a complete listing of all qualifying sorties.

Processing of library data stops when all entries in the index file have been searched.

When the library index has been exhausted, the program prints the statistical summary tables (if requested) and then prepares an output file to the contouring and plotting program, GPCP II. The BOOM-MAP program then terminates. When GPCP II is called, the file prepared by BOOM-MAP (TAPE11) provides a complete input directive list to GPCP. GPCP then produces flight track and contour maps as requested by the user.

The files required for input or output by the BOOM-MAP program are

- 1) Index file "INDEX" - direct access, record length 98
- 2) Database file "LIBRY" - direct access, record length 70
- 3) Two temporary output files TAPE3 and TAPE4 - sequential
- 4) Output file for input to GPCP II program, TAPE11 - sequential

3.2 BOOM-MAP INPUT DATA

This section presents a user's guide for operating the BOOM-MAP program. The guide describes the file of input cards necessary to control a BOOM-MAP run.

The complete run specification consists of three groups of information. These groups are:

- 1) a title card which is printed on all output products.
- 2) qualifiers used to control the particular flights extracted from the library.
- 3) specifiers used to control the particular output products required by the user.

All input file data cards are free format. That is, data is not restricted to particular card columns. Instead, a key word at the beginning of the card specifies the type of data to follow, and parameter values are simply separated by commas in most cases. Spaces between parameters are ignored and if the parameter list exceeds the 80 column allowable card width, the user may continue on the next card without the need for any special continuation characters.

3.2.1 TITLE Card

This card must be the first card in the input file. The key word "TITLE" followed by a space tells the program to accept up to 70 characters for a title. This title will be printed on all output products. The format is:

TITLE title of run

3.2.2 Library Data Qualifier Cards

Access to the information stored in the database library is through the use of qualifier cards. These qualifier cards allow the

user to specify criteria for records that are to be included for analysis. The input file may contain from one to five "packets" of qualifiers, where a packet consists of four of the six available qualifier input cards. The input cards are "SITE", "MISSION", "DATE", "TIME", "AIRCRAFT" and "ACWTN". "ACWTN" is the qualifier to call for aircraft with tail numbers. The input cards must correspond with the following sequence.

"SITE"

"MISSION" or "DATE"

"TIME"

"AIRCRAFT" or "ACWTN"

Each input card is followed by one or more parameters separated by a comma or by the word "ALL". The maximum number of parameters allowed is based on the input card. Note that when specific parameters (e.g., missions, aircraft, etc.) are specified they must match exactly the way they are stored in the library index, character for character. In addition, if a sortie qualifies in more than one way with the user input directives it will still be included only once in the analysis.

CARD I: (SITE)

The SITE card allows the specification of 1 or more MOA site location names in the input file. The user is allowed a maximum of 20 site location names separated by commas. Site names can occur on more than one line if necessary.

Example: SITE Loc 1, Loc 1, Loc 3,...Loc 20

SITE Loc 1, Loc 2,

Loc 3, ...Loc 20

The parameter "ALL" is used when all site locations are to be included.

Example: SITE ALL

CARD II: (MISSION or DATE)

The input card "MISSION" allows the specification of one to ten mission names separated by commas. Mission names may occur on more than one line if necessary.

Example: MISSION Name 1, Name 2,...Name 10

-or-

MISSION Name 1,
Name 2,...Name 10

The parameter "ALL" is used when all Missions are to be included. When the user specifies the "MISSION" card instead of the "DATE" card for input Card II, all dates are considered legal. Once "MISSION" is specified in a packet "DATE" is no longer legal.

The input card "DATE" allows for the specification of one to ten date intervals separated by a comma. Date intervals may occur on more than one line. A date interval consists of a start date followed by a hyphen followed by an end date or simply a start date. All dates must appear as MM/DD/YY format. If only a start date is given, then the end date will be considered identical to the start date.

Example: DATE 01/21/85-02/1/85, 4/8/85,
7/18/86-7/19/86

The parameter "ALL" may be used when all dates are to be included. When the user specifies the "DATE" card instead of the

"MISSION" card as input card II, "MISSION" is no longer legal within that packet.

CARD III (TIME)

The input card "TIME" allows for the specification of one to ten time intervals separated by commas. Time intervals may occur on more than one line. A time interval consists of a start time followed by a hyphen followed by an end time or simply a start time. All times must appear as HHMM format. If only a start time is given, then the end time will default to 2359.

Example TIME: 1100-1200, 1300-1330
1400-1500, 1700

The parameter "ALL" is used when all time intervals are to be included.

CARD IV: AIRCRAFT OR ACWTN

Aircraft may be specified in two ways; either by aircraft type alone, or by a specific aircraft type and tail number.

The input card "AIRCRAFT" allows the specification of one or more aircraft types in the input file. The user is allowed a maximum of ten aircraft types separated by commas. Aircraft types may occur on more than one line. Once "AIRCRAFT" has been specified, "ACWTN" is no longer legal within that packet. The parameter "ALL" may be used when all aircraft types are to be included. When using the parameter "ALL" on the "AIRCRAFT" card, be sure that there are no blank aircraft type entries in INDEX file. If there are INDEX entries without an aircraft type, either specify aircraft type on the "AIRCRAFT" card or use the DELETE program to delete that particular entry in the INDEX file. The aircraft type is required to compute peak overpressure values. Although the program will run, the results may not be accurate. The

aircraft type must exactly match aircraft types in the "INDEX" files. For Example: "F15" will cause an error because it is represented as "F-15" in the "INDEX" files.

Example: AIRCRAFT Type 1, Type 2, Type 3,
 Type 4...

Example: AIRCRAFT ALL

The input card "ACWTN" allows the specification of one or more aircraft types followed by their corresponding tail numbers. The user is allowed a maximum of ten aircraft/tail number pairs separated by commas. Aircraft/tail number pairs may continue on more than one line.

Example: ACWTN AC1 TN1, AC2 TN2,
 AC3 TN3

The parameter "ALL" may be used when all aircraft types and tail numbers are considered legal. Once "ACWTN" has been used, "AIRCRAFT" is no longer considered legal. If the user specified "AIRCRAFT" as input card IV, then all tail numbers are considered to be legal.

3.2.3 Output Product Specification Cards

The type of output data desired by the user is specified by one or more output specification cards. These cards may be entered in any order.

"STATS" Card

This card tells the program to print a full statistics summary. An example of this summary is shown in Tables B-1 through B-5 and includes distribution functions of x, y, and z position variables, effective height, Mach number, and estimated boom strength (directly

below the aircraft). Also included are RMS values of effective height, Mach number, cutoff Mach number, and effective Mach number.

"MACHTRK" Card

This card directs the program to generate a flight track map showing those portions of sortie flight tracks where the aircraft Mach number exceeded 1.0. This card contains one numeric parameter which specifies the map scale ratio. For example, to produce a map of one inch equals 10,000 feet the scale ratio is 120,000.

The smallest scale factor possible is 1:2600 feet dictated by the numerical input limitations to GPCP. The largest realistic scale factor is 1:45,000 feet, giving a plot approximately 5"x 5" in size.

Example: MACHTRK 120000

"BOOMTRK" Card

This card directs the program to generate a flight track map showing those portions of sortie flight tracks where sonic booms were generated which propagated to the ground. This card contains a numeric parameter specifying the map scale ratio. For example, a map of one inch equals 10,000 feet is specified by a scale ratio of 120,000.

Example: BOOMTRK 120000

"CONTOUR" Cards

Contour cards are used to direct the program to produce maps depicting contours of equal boom strength. Three different types of contour maps may be specified: (1) CSEL, (2) CLDN, and (3) peak overpressure, in psf. The CONTOUR cards contain a number of parameters which must be entered in a specific order.

CSEL contour maps are specified using the keyword CONTOUR followed by CSEL. Additional parameters must be separated by commas, and must be input in the following order. The first is the scale ratio of the contour map (see MACHTRK or BOOMTRK cards for a description of the scale ratio). Following the scale ratio at least one (up to a maximum of 20) CSEL contour values must be specified.

Example: CONTOUR CSEL, 120000, 95, 100, 105

Peak overpressure contour maps are specified using the keyword CONTOUR followed by PKOP. Additional parameters must be separated by commas, and are input in the same order as with CSEL contours. The first parameter is the scale ratio of the contour map. Following this parameter must be at least one (up to a maximum of 20) peak overpressure contour values in pounds per square foot. Fractional values are acceptable but the program rounds the user specified values to the nearest tenth of a psf for plotting purposes.

Example: CONTOUR PKOP, 120000, 0.5, 0.8, 1.0, 2.0

CLDN contour maps are specified using the keyword CONTOUR followed by CLDN. Additional parameters must be separated by commas and must be input in the following order. The first parameter is the map scale ratio. The second parameter is the reference number of daytime operations which will be used on a 10 log (N) basis to convert CSEL values to CLDN. Following these two parameters must be at least one (up to a maximum of 19) CLDN contour values to be plotted.

Example: CONTOUR CLDN, 120000, 44.5, 55, 60, 65, 70, 75

"WIDTH" Card

The WIDTH card contains a single parameter which tells the plotting software the paper width (in inches) of the plotting device

used for the map output products. If the paper width is too narrow to accommodate the entire map, the plot software will automatically split the map into several panels which can then be assembled to form the full size map. This card may appear anywhere amongst the output product specification cards or immediately preceding them. The default width if this card is omitted is 34 inches. The default value was changed from 36 inches contained in the original BBN program delivered to the Air Force. Thirty-four inches is the maximum plotting area available on the Tyndall Calcomp plotter.

Example: WIDTH 30

3.2.4 Input Example

The following are examples of input data. The first example is a simple case. The second example shows effective use of the data qualifier cards.

Example 1: Shown below is the input data deck for a relatively simple case:

TITLE	NELLIS MOA -- ALL ACTIVITY
SITE	NELLIS
MISSION	ALL
TIME	ALL
AIRCRAFT	ALL
STATS	
MACHTRK	96000

In this example the title printed on all output is "NELLIS MOA -- ALL ACTIVITY".

The processing software will utilize data only from the NELLIS MOA site. It will, however, select all missions, times of day, and aircraft types. For output products the statistics package will be printed and a map showing flight tracks where aircraft exceeded Mach 1.0 will be plotted to a scale of 1 inch equals 8000 feet.

Example 2: In this example more explicit input qualifiers have been specified.

TITLE	HOLLOMAN MOA
SITE	HOLLOMAN
MISSION	5284711-14DA, 5282717-20GI
TIME	0700-2159
AIRCRAFT	F-15, F-4
SITE	HOLLOMAN
MISSION	5282723-26RO
TIME	0700-2159
AIRCRAFT	ALL
BOOMTRK	9600
CONTOUR	CSEL 96000, 95, 100, 105
CONTOUR	CLDN 9600, 15.2, 65, 70, 75

In this example the title "HOLLOMAN MOA" will be printed on all output products. In contrast to the first example, the program will be fairly selective about the data it extracts from the library. Two packets of data qualifiers are included. Thus the program will select data from the library when either of the two packet conditions are met. It will select data when

- a) the site name is HOLLOMAN, and the mission numbers are 5284711-14DA or 5282717-20GI, and the mission starting time is between 0700 and 2159, and the aircraft type is an F-15 or F-4.

or when

- b) the site name is HOLLOMAN, and the mission name is 5282723-26RO, and the mission starting time is between 0700 and 2159 for any aircraft sortie meeting these conditions.

The output products will include a flight track map of boom producing track segments to a scale of 1 inch equals 8000 feet. Two contour maps will be plotted. The first will be a CSEL contour map to a scale of 1 inch equals 8000 feet, containing the 65, 70, and 75 dB contours. The second will be a CLDN contour map also plotted to a scale of 1 inch equals 8000 feet. The reference number of daily operations is 25.2 sorties and the desired contours are 65, 70 and 75 dB.

3.3 BOOM-MAP File Examples

Table 3.1 shows the JCL and data input for a sample BOOM-MAP case. Only the INDEX and LIBRY files need to be attached. Files TAPE 3 and TAPE 4 are temporary files containing grid data and can be saved if the user desires.

In this sample, TAPE11, the GPCPII plot file is saved for review as file UNIT11. If the user requests statistical output by including the "STATS" card, the output can be printed or saved as a disk file on both. File "BOOMLGO" is the binary executable file of the BOOM-MAP program. File TAPE9T is the executable file used by the CALCOMP plotter to generate the plots.

```

/JOB
SPECTUM.
/USER
CHARGE(*)
SETTL(5000)
SETASL(*)
SETJSL(*)
ATTACH, INDEX=TYNIDEX.
ATTACH, LIBRY=TYNLIB.
ATTACH, LGO=BOOM2GO.
MAP, ON.
MAP, PART.
LDSET(PRESET=ZERO)
LGO.
REWIND, TAPE11.
COPYBF, TAPE11, UNIT11.
STORE, UNIT11.
REWIND, TAPE11.
REWIND, TAPE3.
REWIND, TAPE4.
STORE, TAPE3.
STORE, TAPE4.
ATTACH, GPCP2/UN=APPLLIB/NA.
COPYEI, GPCP2, ABS, VERIFY.
RETURN, GPCP2.
REWIND, ABS.
ABS, TAPE11, JUNK.
REWIND, TAPE9.
COPYEI, TAPE9, TAPE9T, VERIFY.
STORE, TAPE9T.
STORE, JUNK.
DAYFILE.
REWIND, OUTPUT.
ROUTE, OUTPUT, DC=PR.
/EOR
/NOSEQ
TITLE TYNDALL MOA - ALL MISSIONS AS OF 8/21/86
SITE TYNDALL
MISSION ALL
TIME ALL
AIRCRAFT F-4, F-15, F-16, F-18
MACHTRK 300000
MACHTRK 300000
BOOMTRK 300000
CONTOUR CSEL, 300000, 105, 115, 125, 135, 145
CONTOUR PKOP, 300000, 0.5, 1.0, 1.5, 2.0
CONTOUR CLDN, 300000, 10, 55, 65, 75, 85
WIDTH 34.0
STAT
/EOF

```

Table 3.1 Batch file example to run BOOM-MAP.

3.4 BOOM-MAP Output

An example of BOOM-MAP output is shown in Appendix B. Table B-1 depicts the first output page echoes the input specification cards provided by the user. It also summarizes in table form the library qualifier information which will be used to select specific flight data from the library for processing. The second page echoes the specific flights selected from the data base which qualify for processing based on the user supplied input specifications and is shown in Table B-2.

The third page (Table B-3) contains distribution functions of distance, speed, and overpressure variables for times during which the aircraft Mach number is greater than cutoff. Each distribution function contains a number of histogram cells of specified cell size. the first and last cells are underrange and overrange cells used to collect the tails of the distribution which lie outside the expected range of the particular parameter. the remaining cells are of specific parameter range (identified as cell size in the printout).

For example, cell number N extends from

Lower bound = [lower band cell 2] + (N-2) [cell size]

to Upper bound = [lower band cell 2] + (N-1) [cell size]

Each cell contains the number of occurrences of the parameter in the cell range at one second intervals. That is, the number contained in cell N is the number of seconds the parameter was observed in the cell parameter range.

The eleven parameters, defined in Appendix A, are:

- 1) range x-coordinate in feet (range: -132,000 to +132,000 feet)
- 2) range y-coordinate in feet (range: -132,000 to +132,000 feet)
- 3) aircraft height above range center altitude in feet

(range: 750 to 50750 feet)

- 4) aircraft effective height, h_e , above range center altitude
in feet (range: 0 to 50000 feet)
- 5) aircraft Mach number (range: 1.00 to 2.14)
- 6) aircraft cutoff Mach number (range: 1.00 to 2.14)
- 7) aircraft effective Mach number (range: 1.00 to 2.14)
- 8) boom strength overpressure under the projected flight path
in pounds per square foot (range: 0.00 to 14.25 psf)
- 9) boom strength overpressure under the projected flight path
in dB re: 20 micro Pascals (range: 115.0 to 153.5 dB)
- 10) C-weighted sound exposure level under the projected flight
path in dB (range: 90.0 to 128.5 dB)
- 11) A-weighted sound exposure level under the projected flight
path in dB (range: 80.0 to 118.5 dB)

The fourth and fifth pages shown in Table B-4 and B-5 respectively are a combined two-dimensional distribution function of the x/y range coordinates, parameters 1 and 2 on the previous page. This distribution function shows the spatial distribution of aircraft position during boom producing activity. Cells 1 and 52 in both dimensions are the underrange and overrange tails of the distribution. In the x-direction cells 1 through 30 are shown in the first half of the table; cells 31 through 52 in the second half.

Examples of the flight track and contour maps output by GPCP II for four MOAs are also shown. Map annotation in the title block indicates the type of map plotted. Range coordinates are plotted on the left and top of the map, and a cross is plotted at the range center (coordinates $x = 0$, $y = 0$). The y-axis points true north, and

the latitude and longitude of the range center are given in the title block.

REFERENCES

1. Wilby, E., Hornjeff, R., Bishop, E., User's Guide to MOAOPS and BOOM-MAP Computer Programs for Sonic Boom Research, BBN Report 6044, January 1986.

APPENDIX A

MOAOPS PROGRAM OUTPUT EXAMPLES

```

*****
MISSION NAME: 6218-7
MISSION DATE: 03/06/86
SITE LOCATION: 11 TYNDALL
REEL NUMBER: 1
*****

```

MISSION SEGMENT TYPE	STARTING TIME HR MIN SEC	FINISHING TIME HR MIN SEC	A/C NO	A/C TYPE	A/C TAIL NO	SEGMENT DURATION MIN SEC	% TIME SUPERSONIC
1	232 14:33 50.23	15:02 57.95	1	35 F-16	GRIF	29:08	.00
			2	35 F-16	GRIF	29:08	.00
			3	36 F-16	WHAM	29:08	.42
			4	36 F-16	WHAM	29:08	.00

NO OF RECORDS = 2343

*** END OF MISSION TAPE ***

Table A-1. Analysis of Mission Tape Analyzed.

LIBRARY TAPE LISTING, RECORD NO 942 ONWARDS

TIME HR M S	MACH NO	RANGE X	POSITIONS, FT			DIVE/CLIMB ANGLE (DEG)	VELOCITY, FT/SEC			NORMAL ACCEL G
			Y	Z	X		Y	Z		
6218-7		03/06/86	143350	23F-16	GRIF					
11TYNDALL	35	1 1 4	SUP							
15025795		3								
6218-7		03/06/86	143350	23F-16	GRIF					
11TYNDALL	35	1 2 4	SUP							
15025795		3								
6218-7		03/06/86	143350	23F-16	WHAM					
11TYNDALL	36	1 3 4	SUP							
14410965	1.007	35533.	-17596.	16433.	-31.6	517.	-704.	-537.	.067	
14411095	1.045	37268.	-18518.	16287.	-32.8	501.	-716.	-563.	.627	
14411235	1.081	37357.	-19529.	15472.	-33.5	430.	-738.	-532.	1.005	
14411365	1.102	39585.	-20304.	14712.	-33.3	459.	-758.	-535.	.889	
14411495	1.102	39117.	-21549.	13938.	-27.5	400.	-857.	-493.	5.452	
15025795		3								
6218-7		03/06/86	143350	23F-16	WHAM					
11TYNDALL	36	1 4 4	SUP							
15025795		3								

Table A-2. Data Written to the LIBRY File.

Table A-3. Data written to the INDEX File.

[COPY FILE TO LIBRARY TAPE
JUL 77
06/08/21.
09:23:49.
SUPERSONIC ONLY
THANK YOU]

[illegible]

Table A-3. Data written to the INDEX File.


```

*****
* MISSION INDEX FILE *
* UPDATED: 86/09/21. *
* 09.22.50. *
* SUPERSONIC DATA ONLY *
*****

```

MISSION NAME	MISSION DATE	SITE LOCATION
5074-1	03/17/86	TYNDALL
5073-9	03/14/86	TYNDALL
6169-6	06/13/86	TYNDALL
6169-8	06/13/86	TYNDALL
6169-7	06/13/86	TYNDALL
6170-7	06/13/86	TYNDALL
6170-1	06/19/86	TYNDALL
6199-3	07/13/86	TYNDALL
6199-5	07/13/86	TYNDALL
6199-6	07/13/86	TYNDALL
6199-4	07/13/86	TYNDALL
6220-1	08/08/86	TYNDALL
6218-7	08/05/86	TYNDALL

NUMBER OF MISSION TAPES ANALYZED = 13

Table A-4. Data Written to the MINDEX File.

 * INDEX FILE TO LIBRARY TAPE *
 * FULL INDEX: 06/10/13 *
 * 15:14:30 *
 * SUPERSONIC DATA ONLY *

ENTRY NO	MISSION NAME	MISSION DATE	SITE NO	LOCATION	STARTING TIME HR M SEC	FINISHING TIME HR M SEC	A/C TYPE	A/C TAIL NO	STARTING RECORD NO	NO OF RECORDS	NO OF SUPERSONIC RECORDS
1	6100702-SROD	11/16/69	7	HOLLOMAN	0853 4555	0921 1205	22 F-15	137	2	27	24
2	6100702-SROD	11/16/69	7	HOLLOMAN	0853 4555	0921 1205	22 F-15	101	29	102	99
3	6100702-SROD	11/16/69	7	HOLLOMAN	0853 4555	0921 1205	39 F-15	100	131	211	200
4	6100702-SROD	11/16/69	7	HOLLOMAN	0853 4555	0921 1205	39 F-15	121	342	106	103
5	6107003-6/SN	04/17/86	7	HOLLOMAN	1007 0101	1051 0141	22 F-15	150	440	214	211
6	6107003-6/SN	04/17/86	7	HOLLOMAN	1007 0101	1051 0141	22 F-15	124	462	234	231
7	6107003-6/SN	04/17/86	7	HOLLOMAN	1007 0101	1051 0141	22 F-15	117	896	96	93
8	6107003-6/SN	04/17/86	7	HOLLOMAN	1007 0101	1051 0141	22 F-15	145	992	89	86
9	6107701-4/RD	04/17/86	7	HOLLOMAN	1437 0415	1517 3565	21 F-15	096	1001	69	66
10	6107701-4/RD	04/17/86	7	HOLLOMAN	1437 0415	1517 3565	22 F-15	121	1150	163	160
11	6107701-4/RD	04/17/86	7	HOLLOMAN	1437 0415	1517 3565	22 F-15	133	1313	174	171
12	6107701-4/RD	04/17/86	7	HOLLOMAN	1437 0415	1517 3565	22 F-15	101	1407	102	179
13	6007001-4/CO	03/28/86	7	HOLLOMAN	0709 2349	0751 3449	22 F-15	145	1649	60	57
14	6007001-4/CO	03/28/86	7	HOLLOMAN	0709 2349	0751 3449	22 F-15	006	1729	52	49
15	6007001-4/CO	03/28/86	7	HOLLOMAN	0709 2349	0751 3449	22 F-15	116	1701	162	159
16	6007001-4/CO	03/28/86	7	HOLLOMAN	0709 2349	0751 3449	22 F-15	124	1943	130	135
17	5202005-0PAL	10/09/85	7	HOLLOMAN	1324 1051	1350 2351	22 F-15	067	2001	45	42
18	5202005-0PAL	10/09/85	7	HOLLOMAN	1324 1051	1350 2351	22 F-15	135	2126	06	03
19	5202005-0PAL	10/09/85	7	HOLLOMAN	1324 1051	1350 2351	22 F-15	115	2212	37	34
20	5202005-0PAL	10/09/85	7	HOLLOMAN	1324 1051	1350 2351	22 F-15	116	2249	39	36
21	5204711-14DA	10/11/85	7	HOLLOMAN	1145 0627	1223 3077	21 F-15	096	2200	00	03
22	5204711-14DA	10/11/85	7	HOLLOMAN	1145 0627	1223 3077	39 F-4	132	2376	55	52
23	5204711-14DA	10/11/85	7	HOLLOMAN	1145 0627	1223 3077	30 F-4	146	2431	107	104
24	5204711-14DA	10/11/85	7	HOLLOMAN	1145 0627	1223 3077	21 F-15	100	2530	35	32
25	5202723-26RD	10/09/85	7	HOLLOMAN	1533 2373	1605 4623	22 F-15	133	2573	176	173
26	5202723-26RD	10/09/85	7	HOLLOMAN	1533 2373	1605 4623	22 F-15	140	2749	90	87
27	5202723-26RD	10/09/85	7	HOLLOMAN	1533 2373	1605 4623	21 F-15	112	2039	33	30
28	5202723-26RD	10/09/85	7	HOLLOMAN	1533 2373	1605 4623	21 F-15	100	2072	40	45
29	5200721-24	10/07/85	7	HOLLOMAN	1544 0529	1600 0029	21 F-15	097	2920	3	0
30	5200721-24	10/07/85	7	HOLLOMAN	1544 0529	1600 0029	21 F-15	099	2923	55	50
31	5200721-24	10/07/85	7	HOLLOMAN	1544 0529	1600 0029	22 F-15	131	2976	160	165
32	5200721-24	10/07/85	7	HOLLOMAN	1544 0529	1600 0029	22 F-15	119	3144	200	203
33	5202717-2001	10/09/85	7	HOLLOMAN	1247 3511	1321 4519	22 F-15	131	3432	13	10
34	5202717-2001	10/09/85	7	HOLLOMAN	1247 3511	1321 4519	21 F-15	101	3445	43	40
35	5202717-2001	10/09/85	7	HOLLOMAN	1247 3511	1321 4519	21 F-15	134	3400	91	00
36	5202717-2001	10/09/85	7	HOLLOMAN	1247 3511	1321 4519	22 F-15	121	3579	95	92

Table A-5. Full INDEX File for Holloman MOA.

```

*****
* MISSION INDEX FILE *
* UPDATED: 86/10/13 *
* 15:14:30 *
* SUPERSONIC DATA ONLY *
*****

```

MISSION NAME	MISSION DATE	SITE LOCATION
6100702-5ROD	6/69	HOLLOMAN
6107803-6/SN	7/86	HOLLOMAN
6107701-4/RO	7/86	HOLLOMAN
6087801-4/CO	8/86	HOLLOMAN
5282805-8PAL	9/85	HOLLOMAN
5284711-14DA	1/85	HOLLOMAN
5282723-26RO	9/85	HOLLOMAN
5280721-24	7/85	HOLLOMAN
5282717-20GI	9/85	HOLLOMAN

NUMBER OF MISSION TAPES ANALYZED = 9

Table A-6. Mission Index File for Holloman MOA.

 * INDEX FILE TO LIBRARY TAPE *
 * FULL INDEX: 06/10/13 *
 * 15:20:12 *
 * SUPERSONIC DATA ONLY *

ENTRY NO	MISSION NAME	MISSION DATE	SITE NO	LOCATION	STARTING TIME HR M SEC	FINISHING TIME HR M SEC	A/C TYPE	A/C TAIL NO	STARTING RECORD NO	NO OF RECORDS	NO OF SUPERSONIC RECORDS
1	4863-11	03/04/86	5	LUKE	1236 0305	1252 5105	28 F-16	001	2	04	01
2	4863-11	03/04/86	5	LUKE	1236 0305	1252 5105	28 F-16	002	86	53	50
3	4863-11	03/04/86	5	LUKE	1236 0305	1252 5105	46	01	139	3	0
4	4863-11	03/04/86	5	LUKE	1236 0305	1252 5105	47	02	142	3	0
5	4863-11	03/04/86	5	LUKE	1236 0305	1252 5105	7 F-14	03	145	33	30
6	4863-11	03/04/86	5	LUKE	1236 0305	1252 5105	7 F-14	04	170	37	34
7	4862-11	03/03/86	5	LUKE	1150 1453	1223 1293	28 F-16	330	215	3	0
8	4862-11	03/03/86	5	LUKE	1150 1453	1223 1293	28 F-16	311	210	231	220
9	4862-11	03/03/86	5	LUKE	1150 1453	1223 1293	47	100	449	19	16
10	4862-11	03/03/86	5	LUKE	1150 1453	1223 1293	47	113	460	0	5
11	4863-4	03/04/86	5	LUKE	0835 4773	0857 3023	22 F-15	5067	476	40	45
12	4863-4	03/04/86	5	LUKE	0835 4773	0857 3023	22 F-15	5049	524	37	34
13	4863-4	03/04/86	5	LUKE	0835 4773	0857 3023	32 F-10	303	561	20	17
14	4863-4	03/04/86	5	LUKE	0835 4773	0857 3023	32 F-10	304	581	57	54
15	4862-8	03/03/86	5	LUKE	1020 5497	1055 5107	30 F-15	7164	630	125	122
16	4862-8	03/03/86	5	LUKE	1020 5497	1055 5107	22 F-15	6102	763	3	0
17	4862-8	03/03/86	5	LUKE	1020 5497	1055 5107	32 F-10	302	766	3	0
18	4862-8	03/03/86	5	LUKE	1020 5497	1055 5107	32 F-10	300	769	43	40
19	5196-10	07/15/85	5	LUKE	1520 5099	1530 4059	22 F-15	7163	012	4	1
20	5196-10	07/15/85	5	LUKE	1530 4069	1557 1441	22 F-15	7163	016	52	49
21	5196-10	07/15/85	5	LUKE	1520 5099	1530 4059	0	5049	060	3	0
22	5196-10	07/15/85	5	LUKE	1530 4069	1557 1441	22 F-15	5049	071	72	69
23	5196-10	07/15/85	5	LUKE	1520 5099	1530 4059	15 A-7	406	943	3	0
24	5196-10	07/15/85	5	LUKE	1530 4069	1557 1441	15 A-7	406	946	3	0
25	5196-10	07/15/85	5	LUKE	1520 5099	1530 4059	15 A-7	210	949	3	0
26	5196-10	07/15/85	5	LUKE	1530 4069	1557 1441	15 A-7	210	952	3	0
27	5203-15	07/22/85	5	LUKE	1356 4435	1420 1971	20 F-16	110	955	50	47
28	5203-15	07/22/85	5	LUKE	1356 4435	1420 1971	20 F-16	124	1005	143	140
29	5203-15	07/22/85	5	LUKE	1356 4435	1420 1971	40 F-4	6553	1140	169	166
30	5203-15	07/22/85	5	LUKE	1356 4435	1420 1971	40 F-4	519	1317	139	136
31	5203-15	07/22/85	5	LUKE	1356 4435	1420 1971	40 F-4	432	1456	101	170
32	5203-15	07/22/85	5	LUKE	1356 4435	1420 1971	40 F-4	677	1637	91	80
33	5197-5-DACT	07/16/85	5	LUKE	0054 0247	0933 1957	22 F-15	5047	1720	115	112
34	5197-5-DACT	07/16/85	5	LUKE	0054 0247	0933 1957	22 F-15	1063	1043	110	115
35	5197-5-DACT	07/16/85	5	LUKE	0054 0247	0933 1957	20 F-16	124	1961	106	103
36	5197-5-DACT	07/16/85	5	LUKE	0054 0247	0933 1957	20 F-16	110	2067	25	22
37	5203-5-DACT	07/22/85	5	LUKE	0059 2793	0027 2793	22 F-15	5049	2072	3	0
38	5203-5-DACT	07/22/85	5	LUKE	0027 2793	0059 2793	22 F-15	5---	2095	3	0
39	5203-5-DACT	07/22/85	5	LUKE	0059 2793	0034 4003	22 F-15	5049	2090	40	37
40	5203-5-DACT	07/22/85	5	LUKE	0059 2793	0027 2793	20 F-16	124	2130	3	0
41	5203-5-DACT	07/22/85	5	LUKE	0027 2793	0059 2793	20 F-16	1	2141	3	0
42	5203-5-DACT	07/22/85	5	LUKE	0059 2793	0034 4003	20 F-16	124	2144	47	44
43	5203-5-DACT	07/22/85	5	LUKE	0059 2793	0027 2793	20 F-16	110	2191	3	0
44	5203-5-DACT	07/22/85	5	LUKE	0027 2793	0059 2793	20 F-16	1	2194	3	0
45	5203-5-DACT	07/22/85	5	LUKE	0059 2793	0034 4003	20 F-16	110	2197	102	99

Table A-7. Full INDEX File for Luke MOA.

```

*****
* MISSION INDEX FILE *
* UPDATED: 86/10/13 *
* 15:20:12 *
* SUPERSONIC DATA ONLY *
*****

```

MISSION NAME	MISSION DATE	SITE LOCATION
6063-11	4/86	LUKE
6062-11	3/86	LUKE
6063-4	4/86	LUKE
6062-8	3/86	LUKE
5196-18	5/85	LUKE
5203-15	2/85	LUKE
5197-5-DACT	6/85	LUKE
5203-5-DACT	2/85	LUKE

NUMBER OF MISSION TAPES ANALYZED = 8

Table A-8. Mission INDEX File for Luke MOA.

 * INDEX FILE TO LIBRARY TAPE *
 * FULL INDEX: 86/10/13 *
 * 15:46:40 *
 * SUPERSONIC DATA ONLY *

ENTRY NO	MISSION NAME	MISSION DATE	SITE NO	LOCATION	STARTING TIME HR M SEC	FINISHING TIME HR M SEC	A/C TYPE	A/C TAIL NO	STARTING RECORD NO	NO OF RECORDS	NO OF SUPERSONIC RECORDS
1	6024-DACT-1130	01/24/86	1	NELLIS	1128 4349	1147 5809	9 F-5	MIG	2	3	0
2	6024-DACT-1130	01/24/86	1	NELLIS	1128 4349	1147 5809	9 F-5	MIG	5	3	0
3	6024-DACT-1130	01/24/86	1	NELLIS	1128 4349	1147 5809	21 F-15	RING	8	3	0
4	6024-DACT-1130	01/24/86	1	NELLIS	1128 4349	1147 5809	21 F-15	RING	11	3	0
5	6006-DACT-0830	01/06/86	1	NELLIS	0833 4315	0857 4145	9 F-5	MIG	14	20	17
6	6006-DACT-0830	01/06/86	1	NELLIS	0833 4315	0857 4145	9 F-5	MIG	34	35	32
7	6006-DACT-0830	01/06/86	1	NELLIS	0833 4315	0857 4145	28 F-106	COBR	69	3	0
8	6006-DACT-0830	01/06/86	1	NELLIS	0833 4315	0857 4145	29 F-106	COBR	72	3	0
9	6170-DACT-1230	06/19/86	1	NELLIS	1236 4061	1259 0001	9 F-5	MIG	75	14	11
10	6170-DACT-1230	06/19/86	1	NELLIS	1236 4061	1259 0001	9 F-5	MIG	89	3	0
11	6170-DACT-1230	06/19/86	1	NELLIS	1236 4061	1259 0001	29 F-106	WOLF	92	3	0
12	6170-DACT-1230	06/19/86	1	NELLIS	1236 4061	1259 0001	29 F-106	WOLF	95	3	0
13	6170-DACT-1200	06/19/86	1	NELLIS	1201 2683	1230 1473	9 F-5	MIG	98	69	66
14	6170-DACT-1200	06/19/86	1	NELLIS	1201 2683	1230 1473	9 F-5	MIG	167	17	14
15	6170-DACT-1200	06/19/86	1	NELLIS	1201 2683	1230 1473	29 F-106	SNAK	184	11	8
16	6170-DACT-1200	06/19/86	1	NELLIS	1201 2683	1230 1473	29 F-106	SNAK	195	47	44

Table A-9. Full INDEX File for Nellis MOA.

 * MISSION INDEX FILE *
 * UPDATED: 86/10/13 *
 * 15:46:40 *
 * SUPERSONIC DATA ONLY *

MISSION NAME	MISSION DATE	SITE LOCATION
6024-DACT-1130	4/86	NELLIS
6006-DACT-0830	6/86	NELLIS
6170-DACT-1230	9/86	NELLIS
6170-DACT-1200	9/86	NELLIS

NUMBER OF MISSION TAPES ANALYZED = 4

Table A-10. Mission INDEX File for Nellis MOA.

 * INDEX FILE TO LIBRARY TAPE *
 * FULL INDEX: 06/10/13 *
 * 15:45:05 *
 * SUPERSONIC DATA ONLY *

ENTRY NO	MISSION NAME	MISSION DATE	SITE NO	LOCATION	STARTING TIME HR M SEC	FINISHING TIME HR M SEC	A/C TYPE	A/C TAIL NO	STARTING RECORD NO	NO OF RECORDS	NO OF SUPERSONIC RECORDS
1	LAA603120639	03/12/86	3	OCEANA	0919 5436	0947 2212	39 F-4	94TH	2	13	10
2	LAA603120639	03/12/86	3	OCEANA	0919 5436	0947 2212	36 F-14	94TH	15	67	64
3	LAA603120639	03/12/86	3	OCEANA	0919 5436	0947 2212	59	VF-4	82	21	18
4	LAA603120639	03/12/86	3	OCEANA	0919 5436	0947 2212	58	VF-4	103	46	43
5	LAA603120639	03/12/86	3	OCEANA	0919 5436	0947 2212	59	VF-4	149	55	52
6	LAA603100619	03/10/86	3	OCEANA	0939 5975	1121 5513	39 F-4	71ST	204	257	254
7	LAA603110630	03/11/86	3	OCEANA	0914 1392	0918 2065	36 F-14	94TH	461	3	0
8	LAA603110630	03/11/86	3	OCEANA	0918 2095	0944 4429	36 F-14	94TH	464	3	0
9	LAA603110630	03/11/86	3	OCEANA	0914 1392	0918 2065	39 F-4	94TH	467	3	0
10	LAA603110630	03/11/86	3	OCEANA	0918 2095	0944 4429	36 F-14	94TH	470	3	0
11	LAA603110630	03/11/86	3	OCEANA	0914 1392	0918 2065	59	VF-4	473	3	0
12	LAA603110630	03/11/86	3	OCEANA	0918 2095	0944 4429	59	VF-4	476	52	49
13	LAA603110630	03/11/86	3	OCEANA	0914 1392	0918 2065	59	VF-4	528	3	0
14	LAA603110630	03/11/86	3	OCEANA	0918 2095	0944 4429	59	VF-4	531	7	4
15	LAA603110630	03/11/86	3	OCEANA	0914 1392	0918 2065	59	VF-4	538	3	0
16	LAA603110630	03/11/86	3	OCEANA	0918 2095	0944 4429	59	VF-4	541	4	1

Table A-11. Full INDEX File for Oceana MOA.

 * MISSION INDEX FILE *
 * UPDATED: 06/10/13 *
 * 15:45:05 *
 * SUPERSONIC DATA ONLY *

MISSION NAME	MISSION DATE	SITE LOCATION
LAA603120639	2/86	OCEANA
LAA603100619	07/86	OCEANA
LAA603110630	1/86	OCEANA

NUMBER OF MISSION TAPES ANALYZED = 3

Table A-12. Mission INDEX File for Oceana MOA.

 • INDEX FILE TO LIBRARY TAPE •
 • FULL INDEX: 06/10/13 •
 • 15:47:00 •
 • SUPERSONIC DATA ONLY •

ENTRY NO	MISSION NAME	MISSION DATE	SITE NO	LOCATION	STARTING TIME HR M SEC	FINISHING TIME HR M SEC	A/C TYPE	A/C TAIL NO	STARTING RECORD NO	NO OF RECORDS	NO OF SUPERSONIC RECORDS
1	6074-1	03/17/86	11	TYNDALL	0740 1463	0743 1773	35 F-16	LANC	2	3	0
2	6074-1	03/17/86	11	TYNDALL	0743 1923	0759 3633	32 F-15	LANC	3	3	0
3	6074-1	03/17/86	11	TYNDALL	0740 1463	0743 1773	35 F-16	LANC	8	3	0
4	6074-1	03/17/86	11	TYNDALL	0743 1923	0759 3633	35 F-16	LANC	11	3	0
5	6074-1	03/17/86	11	TYNDALL	0740 1463	0743 1773	35 F-16	LANC	14	3	0
6	6074-1	03/17/86	11	TYNDALL	0743 1923	0759 3633	35 F-16	LANC	17	3	0
7	6074-1	03/17/86	11	TYNDALL	0740 1463	0743 1773	35 F-16	LANC	20	3	0
8	6074-1	03/17/86	11	TYNDALL	0743 1923	0759 3633	35 F-16	LANC	23	3	0
9	6073-9	03/14/86	11	TYNDALL	1522 4613	1549 4333	32 F-15	LANC	26	3	0
10	6073-9	03/14/86	11	TYNDALL	1522 4613	1549 4333	35 F-16	LANC	29	10	7
11	6073-9	03/14/86	11	TYNDALL	1522 4613	1549 4333	35 F-16	LANC	39	17	14
12	6073-9	03/14/86	11	TYNDALL	1522 4613	1549 4333	35 F-16	LANC	56	4	1
13	6073-9	03/14/86	11	TYNDALL	1522 4613	1549 4333	35 F-16	LANC	68	3	0
14	6169-6	06/18/86	11	TYNDALL	1117 5631	1146 4411	16 F-4	CHBT	63	3	0
15	6169-6	06/18/86	11	TYNDALL	1117 5631	1146 4411	19 F-4	CHBT	66	11	8
16	6169-8	06/18/86	11	TYNDALL	1353 0243	1429 3823	35 F-16	GRIF	77	5	2
17	6169-8	06/18/86	11	TYNDALL	1353 0243	1429 3823	32 F-15	GRIF	82	84	81
18	6169-8	06/18/86	11	TYNDALL	1353 0243	1429 3823	35 F-16	GRUD	166	7	4
19	6169-8	06/18/86	11	TYNDALL	1353 0243	1429 3823	32 F-15	GRUD	173	3	0
20	6169-7	06/18/86	11	TYNDALL	1387 5919	1339 0999	32 F-15	LANC	176	3	0
21	6169-7	06/18/86	11	TYNDALL	1387 5919	1339 0999	35 F-16	LANC	179	3	0
22	6169-7	06/18/86	11	TYNDALL	1387 5919	1339 0999	32 F-15	LANC	182	3	0
23	6169-7	06/18/86	11	TYNDALL	1387 5919	1339 0999	32 F-15	LANC	185	3	0
24	6170-7	06/19/86	11	TYNDALL	1221 2169	1259 2229	32 F-15	CUBI	188	3	0
25	6170-7	06/19/86	11	TYNDALL	1221 2169	1259 2229	35 F-16	CUBI	191	3	0
26	6170-7	06/19/86	11	TYNDALL	1221 2169	1259 2229	16 F-4	CHBT	194	3	0
27	6170-7	06/19/86	11	TYNDALL	1221 2169	1259 2229	16 F-4	CHBT	197	21	19
28	6170-1	06/19/86	11	TYNDALL	0740 3083	0818 2453	35 F-16	YUKO	218	89	86
29	6170-1	06/19/86	11	TYNDALL	0740 3083	0818 2453	32 F-15	YUKO	387	146	143
30	6170-1	06/19/86	11	TYNDALL	0740 3083	0818 2453	16 F-4	CHBT	433	37	34
31	6170-1	06/19/86	11	TYNDALL	0740 3083	0818 2453	19 F-4	CHBT	490	7	4
32	6199-3	07/18/86	11	TYNDALL	0927 1383	1000 2283	35 F-16	SPIK	497	221	218
33	6199-3	07/18/86	11	TYNDALL	0927 1383	1000 2283	32 F-15	SPIK	718	52	49
34	6199-3	07/18/86	11	TYNDALL	0927 1383	1000 2283	4 A-4	SPIK	778	3	0
35	6199-3	07/18/86	11	TYNDALL	1350 3537	1356 2627	32 F-15	AUDI	773	3	0
36	6199-3	07/18/86	11	TYNDALL	1356 2757	1422 3867	35 F-16	AUDI	776	47	44
37	6199-3	07/18/86	11	TYNDALL	1350 3537	1356 2627	32 F-15	GRND	823	3	0
38	6199-3	07/18/86	11	TYNDALL	1356 2757	1422 3867	32 F-15	GRND	826	17	14
39	6199-3	07/18/86	11	TYNDALL	1350 3537	1356 2627	4 A-4	AUDI	843	3	0
40	6199-3	07/18/86	11	TYNDALL	1356 2757	1422 3867	4 A-4	AUDI	846	3	0
41	6199-3	07/18/86	11	TYNDALL	1350 3537	1356 2627	2 A-4	GRND	849	3	0
42	6199-3	07/18/86	11	TYNDALL	1356 2757	1422 3867	2 A-4	GRND	852	3	0
43	6199-6	07/18/86	11	TYNDALL	1441 5543	1516 0403	35 F-16	YUCC	855	22	19
44	6199-6	07/18/86	11	TYNDALL	1441 5543	1516 0403	32 F-15	YUCC	877	3	0
45	6199-6	07/18/86	11	TYNDALL	1441 5543	1516 0403	32 F-15	YUCC	880	47	44
46	6199-4	07/18/86	11	TYNDALL	1384 3875	1327 4285	32 F-15	LANC	927	3	0
47	6199-4	07/18/86	11	TYNDALL	1384 3875	1327 4285	35 F-16	LANC	930	3	0
48	6220-1	08/08/86	11	TYNDALL	0858 0299	0928 0289	35 F-16	BACO	933	3	0
49	6220-1	08/08/86	11	TYNDALL	0858 0299	0928 0289	35 F-16	BACO	936	3	0
50	6220-1	08/08/86	11	TYNDALL	0858 0299	0928 0289	32 F-15	BACO	939	3	0
51	6218-7	08/06/86	11	TYNDALL	1433 5823	1582 5795	35 F-16	GRIF	942	3	0
52	6218-7	08/06/86	11	TYNDALL	1433 5823	1582 5795	35 F-16	GRIF	945	3	0
53	6218-7	08/06/86	11	TYNDALL	1433 5823	1582 5795	36 F-16	MMHM	948	8	5
54	6218-7	08/06/86	11	TYNDALL	1433 5823	1582 5795	36 F-16	MMHM	956	3	0
55	6219-3	08/07/86	11	TYNDALL	1081 1855	1020 3615	35 F-16	INDE	959	13	10
56	6219-3	08/07/86	11	TYNDALL	1081 1855	1020 3615	32 F-15	INDE	972	14	11
57	6223-1	08/11/86	11	TYNDALL	0755 0737	0826 1587	35 F-16	TANK	986	111	108
58	6223-1	08/11/86	11	TYNDALL	0755 0737	0826 1587	35 F-16	TANK	1097	99	96
59	6223-1	08/11/86	11	TYNDALL	0755 0737	0826 1587	36 F-16	KARA	1196	84	81
60	6223-1	08/11/86	11	TYNDALL	0755 0737	0826 1587	36 F-16	KARA	1288	65	62

Table A-13. Full INDEX File for Tyndall MOA.


```

*****
* MISSION INDEX FILE *
*   UPDATED: 86/10/13   *
*       15:47:00       *
* SUPERSONIC DATA ONLY *
*****

```

MISSION NAME	MISSION DATE	SITE LOCATION
6074-1	7/86	TYNDALL
6073-9	4/86	TYNDALL
6169-6	8/86	TYNDALL
6169-8	8/86	TYNDALL
6169-7	8/86	TYNDALL
6170-7	9/86	TYNDALL
6170-1	9/86	TYNDALL
6199-3	8/86	TYNDALL
6199-5	8/86	TYNDALL
6199-6	8/86	TYNDALL
6199-4	8/86	TYNDALL
6220-1	8/86	TYNDALL
6218-7	6/86	TYNDALL
6219-3	7/86	TYNDALL
6223-1	1/86	TYNDALL

NUMBER OF MISSION TAPES ANALYZED = 15

Table A-14. Mission INDEX File for Tyndall MOA.

APPENDIX B

BOOM-MAP PROGRAM OUTPUT EXAMPLES

NOTE: ALL PLOTS HAVE BEEN REDUCED AND
THE SCALE IS INCORRECT

SOURCE LISTING:

1: TITLE TYNDALL MOA - ALL MISSIONS AS OF 3/03/86
 2: SITE TYNDALL
 3: MISSION 6073-9, 6170-7, 6199-5, 6199-6, 6199-4, 6216-7, 6219-3, 6223-1
 4: TIME ALL
 5: AIRCRAFT F-4, F-15, F-16
 6: MACHTRK 300000
 7: 900MTRK 300000
 8: CONTOUR CSEL: 300000, 95, 100, 105
 9: CONTOUR PKOP: 300000, 0.6, 0.3, 1.0, 2.0
 10: CONTOUR CLON: 300000, 45, 55, 65, 75
 11: WIDTH 36.0
 12: STAT

TABLE 1/1

LOCATION	EXERCISE NAME	DATE (YYMMDD-YYMMDD)	TIME (HHMM-HHMM)	AIRCRAFT TYPE	TAIL NUMBER
TYNDALL	6073-9	ALL	ALL	F-4	ALL
	6170-7			F-15	ALL
	6199-5			F-16	ALL
	6199-6				
	6199-4				
	6216-7				
	6219-3				
	6223-1				

Table B-1. Page 1 of BOOM-MAP Output.

TITLE: WINDCELL NO. 1 - CELL MISSIONS AS OF 3/31/85														
X-Z-LEVEL			LOWER BOUND CELL 2 = -132000.0			CELL SIZE = 5200.000								
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Y-LEVEL			LOWER BOUND CELL 2 = -132000.0			CELL SIZE = 5200.000								
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Z-LEVEL			LOWER BOUND CELL 2 = .0			CELL SIZE = 1000.000								
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
EFFECTIVE HEIGHT			LOWER BOUND CELL 2 = .0			CELL SIZE = 1000.000			RMS = 29473.485					
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
MACH NUMBER			LOWER BOUND CELL 2 = 1.0			CELL SIZE = .020			RMS = 1.191					
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
CUTOFF MACH NO.			LOWER BOUND CELL 2 = 1.0			CELL SIZE = .020			RMS = 1.130					
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
EFFECTIVE MACH NO.			LOWER BOUND CELL 2 = 1.0			CELL SIZE = .020			RMS = 1.255					
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
OVERPRESSURE (PSI)			LOWER BOUND CELL 2 = .0			CELL SIZE = .250								
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
PEAK LEVEL			LOWER BOUND CELL 2 = 115.0			CELL SIZE = .500								
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
C-LEVEL			LOWER BOUND CELL 2 = 90.0			CELL SIZE = .500								
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
A-LEVEL			LOWER BOUND CELL 2 = 80.0			CELL SIZE = .500								
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
TIME GREATER THAN MACH 1.0 (SEC) = 630 TIME GREATER THAN CUTOFF MACH NO (SEC) = 112														

Table B-3. Page 3 of BOOM-MAP Output.

[illegible]

[illegible]

Table B-5. Page 5 of BOOM-MAP Output.




Figure B-1.




Figure B-2.




Figure B-3.




Figure B-5.




Figure B-6.




Figure B-7.




Figure B-8.




Figure B-9.




Figure B-10.




Figure B-11.




Figure B-12.




Figure B-13.




Figure B-14.




Figure B-15.




Figure B-16.




Figure B-17.




Figure B-18.




Figure B-19.




Figure B-20.

END

DATE

FILMD

3-88

DTIC